



Shandong Shengrun Automobile Co., Ltd

Tongya road NO.1, Quanpu industrial area Liangshan County, Shandong Province, China
 Mobile: +86 15805376335 | Tel: +86-537-7608666 | jonah@shengrunauto.cn

QUOTATION SHEET



Quotation NO.: SR220204JL02

Date: 2022.02.12

Item	Description of Vehicles	Quantity	Price Term	Unit Price	Total Amount
1.	3 Axles 61,900 Liters LPG Tanker Semitrailer - Mechanical Suspension	10 Units	FOB Tianjin	US\$	US\$
			CIF Lome/Tema	US\$	US\$
2.	3 Axles 61,900 Liters LPG Tanker Semitrailer - Pneumatic Suspension	10 Units	FOB Tianjin	US\$	US\$
			CIF Lome/Tema	US\$ 0	US\$

Currency: 1 USD = 6.3 RMB

Quotation valid date: 15 days

Terms & Conditions:

Delivery time	Production time 55 workdays after deposit payment received. 58 workdays ready to ship at China port.
Package & Shipment	1 Unit per package by Tractor truck, Shipment by Bulk Ship or Ro-ro Ship
Warranty & After-sale service	12 Months warranty for main beam and tank body. We'll provide qualified spare parts with the price we get from our suppliers, and sent engineer for maintenance if necessary.
Payment terms	30% Deposit by T/T within 3 days after order confirmed. 70% Balance payment by T/T before delivery from factory.





Shandong Shengrun Automobile Co., Ltd

Tongya road NO.1, Quanpu industrial area Liangshan County, Shandong Province, China
 Mobile: +86 15805376335 | Tel: +86-537-7608666 | jonah@shengrunauto.cn

Specifications:

	Type	61,900 Liters LPG tank semi trailer, Single compartment
	Usage	Hauling LPG(liquefied petroleum gas.)
Weight	Tare Weight	Approx. 14.1 Tons
	Loading capacity	Effective volume 61,900 Liters, +3% vapor space
	Gross weight	40000 kg
	Payload	25998 kg (Liquid Density: 420 kg/m ³)
Dimensions	Outside Dimension	13580*2540*4000 mm (Final dimension depend on the final design)
	Wheel base	7350+1310+1310mm
Tank Body	Design/welding Technology	Heavy duty and extra durability designed; "T" main beam welding by automatic Submerged-Arc processes.
	Tank body	Material Q420R steel, Tank shell thickness 10mm, Corrosion allowance 1mm
	Tank End/Head	Q345R Steel plate, Ellipsoidal front head 9mm thickness, Ellipsoidal Rear head 10mm thickness
	Loading / Discharge Valve	4 Pcs ball valve, 2 Pcs for Gas phase(DN25) discharging, 2 Pcs for liquid phase(DN50) discharging, fixed into the valve box, with quick-plug connections. Bottom loading and discharging.
	Emergency valve	1 Set Gas phase emergency cut off valve(DN25) at bottom of the tank, Hand wheel remote control(operate at valve box); 1 Set Liquid phase emergency cut off valve (DN50) at bottom of the tank, Hand wheel remote control(operate at valve box).
	Pressure Relief	1 Emergency pressure relief, fixed at the rear of tank
	Manhole Cover	16MnIII, at top of the tank
	Safety Valve	1 Pc, Built-in and full lift, fixed at top of tank
	Thermometer	2 Pcs, fixed into valve box.
	Pressure Gauge	2 Pcs, fixed into valve box
	Liquid level meter	1 Pc, Float level gauge, at rear of tank
	Working Pressure	≤1.6MPa (Design pressure 1.6Mpa)
	Working Temperature	-20~50℃ (Design Temperature 50℃)
	Water pressure test	2.1MPa (Air-leakage test 1.61MPa)
OEM parts	King Pin	3.5"(90#) bolts type king pin fixed to High Tensile Steel Plate
	Landing Gear	28 Tons manual operation with two speed
	Axle	3 axles * 13 tons, square axle FUWA brand (Chinese best)
	Suspension	Heavy duty tri-axle Pneumatic suspension / Mechanical suspension





Shandong Shengrun Automobile Co., Ltd

Tongya road NO.1, Quanpu industrial area Liangshan County, Shandong Province, China
 Mobile: +86 15805376335 | Tel: +86-537-7608666 | jonah@shengrunauto.cn

	Brake system	Dual line air brake system, 6 double brake chambers; Wide brake pads, 45 Liters air tank; Reliable Automatic transformer Relay valve
	ABS	Equipped 4S/2M KORMEE brand
	Rim	9.0*22.5 Steel Rim, (Aluminum alloy rim optional) 12 Pcs + 1 spare
	Tire	Triangle brand 12.00R22.5 tire, 12 Pcs + 1 spare
Accessories	Fire extinguisher	2 Pcs *8 kgs fire extinguisher with box at rear part
	Rear&Side Guard	Side guard+Rear guard+Mud guard+ Anti Static device
	Spare Tire Carrier	2 sets spare wheel carriers, including a riser.
	Valve Box	2 Pcs steel Valve box with lock.
	Tools Box	One piece steel tool box with lock.
Electrical	One unit of 24V 7-Pin ISO 1185 socket; LED light (Standard rear light, side light, rear reflector, side light, side reflector etc.)	
Painting	Sand blasting to SA 2.5 before painting; one coats of Epoxy zinc phosphate primer, anti-corrosion; two coats of finish painting; Polyurethane paint . Color optional.	
Approvals / Standard	Supervision Regulations on Safety Technology for Transportable Pressure Vessel (TSG R0005-2011); Pressured Vessel (GB150.1-4-2011), GB/T19905-2017 <LPG Trailer>	

* Notes:

1. The above dimension and weight will be adjusted according to the tractor specifications and actual production design.
2. All the details not mentioned above should comply with Chinese regulations.
3. If any components or structure changed, the price shall be modified accordingly.



SHENGRUN AUTO
 Since 1982. Double safety Tanker



Shandong Shengrun Automobile Co., Ltd

Tongya road NO.1, Quanpu industrial area Liangshan County, Shandong Province, China
Mobile: +86 15805376335 | Tel: +86-537-7608666 | jonah@shengrunauto.cn

Pictures and Details



SHENGRUN AUTO
Since 1982. Double safety Tanker

- Anti-fracture
- Anti-damage
- Anti-leakage
- Anti-vibration
- Anti-rollover